

GT720 - GameTime Projector

The Ultimate Gaming Projector

Enjoy the ultimate in widescreen entertainment with Optoma's GT720 Gaming projector. Designed for flawless performance with today's top HD consoles and gaming PCs, the GT720 energizes games with stunning speed, high contrast and vivid colors. Widescreen display provides cinema-sized fun with a whopping 300" maximum screen size. The portable GT720 comes with its own backpack for on-the-go gaming convenience.

* 3D content can be viewed with DLP®Link™ 3D glasses when the projector is connected to a computer with a compatible 3D graphics card. Please visit www.optoma.com for more information.



Features

- Bright at 2500 ANSI lumens with a high contrast ratio of 3000:1
- Projects a 150" diagonal image less than eight feet away
- Supports resolutions up to 1080p
- Powerful audio – built-in 10-watt speaker system
- Flexible connections – HDMI, VGA, S-video, Composite, Stereo RCA Audio-in, Stereo Audio-out & RS-232

Specifications

Display Technology

0.65" DC3 DMD DLP® Technology by Texas Instruments

Native Resolution

WXGA (1280 x 800)

Maximum Resolution

UXGA (1600 x 1200), 1080p

Brightness

2500 ANSI Lumens

Contrast Ratio

3000:1 (Full On/Full Off)

Lamp Life and Type

5000/3000 Hours (STD/Bright)
180W P-VIP

Throw Ratio

0.72:1 (Distance/Width)

Image Size (Diagonal)

34" to 300" (0.86m to 7.62m)

Projection Distance

1.64' to 18.0' (0.5m to 5.48m)

Remote Control

IR Remote Control

Aspect Ratio

16:10 Native, 16:9 & 4:3 Compatible

Keystone Correction

± 15° Vertical

Audio

Two 5-Watt Speakers

Uniformity

85%

Computer Compatibility

UXGA, SXGA+, WXGA, SXGA, VGA, SVGA, VESA, PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM, EDTV (480p), HDTV (576i/p, 720i/p, 1080i/p)

3D Compatibility

120Hz frame sequential 3D for resolutions up to 720p, 60Hz field sequential 3D for resolutions up to 480i

Projection Lens

F=2.55, f=10.19

Projection Method

Front, Rear, Ceiling Mount, Table Top

User Controls

Complete On-Screen Menu Adjustments in 20 Languages

Security

One Kensington® Lock, Security Bar and Keypad Lock

I/O Connectors

HDMI, VGA-In, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-Out and RS-232

Dimensions (W x H x D)

12.76" x 3.82" x 9.21"
(324 x 97 x 234 mm)



Weight

6.5 lbs (2.95 kg)

Noise Level (STD/Bright)

28dB/30dB

Operating Temperature

41-104°F (5-40°C) (80% Max Humidity), Adjustable Fan Speed for High Altitude Application

Power Supply

AC Input 100 - 240V, 50-60Hz, Auto-Switching

Power Consumption

255W (Bright), 233 Watts (STD) <1 Watt (Standby)

Standard Accessories

AC Power Cord, Backpack, VGA to Component Adapter, Remote Control, Batteries for Remote, Lens Cap, CD-ROM User's Manual, Quick Start Card and Multilingual Warranty Card

Optional Accessories

Carrying Case, Ceiling Mount, VGA Cable, Composite Cable, S-Video Cable and Panoview™ Series Screens

Warranty

1 Year Limited Parts and Labor, 90 Days on Lamp

UPC

796435 81 116 7