

CASIO LAMP FREE PROJECTORS

- Low Total Cost of Ownership
- Eco Friendly Lamp Change "Down Time" Eliminated



PRO LINE XJ-H2650

3500 LUMENS • WXGA (1280 X 800) • 1.2X ZOOM • USB • WLAN

The Casio Pro series projectors with 4000 lumen brightness provides the brightness and performance needed for the largest rooms.

WHITEBOARD READY

Casio Pro series projectors are interactive whiteboard ready, using an optional Interactive Pen with any white surface, whether whiteboard, screen



or wall. Use the Interactive Pen as a PC mouse to scroll and click through software applications or as a pen to draw, write and annotate images. You can touch the screen as you would with a marker or use it from a distance, even with screens so large that you can't reach the entire surface. Choose a Pro series projector to minimize shadows, whether it is wall or ceiling mounted or on an AV cart. No special software needed. No calibration required.

IP NETWORK DIGITAL SIGNAGE CONNECTIVITY

Tie Casio Pro series models into your IP network for remote control and maintenance. These projectors each include a standard RJ-4511 Ethernet connection and related firmware.



3-D READY

3D is not just for scientists or movie fans. It can provide dramatic impact for business

dramatic impact for business presentations— and research has shown that it can help students better engage with their lessons and it can lead to better academic performance. All Casio Pro models include 3D capability. Optional 2D-3D software can help you convert standard presentations to 3D. (3D glasses and software required and sold separately.)

MOBISHOW® (Smartphone compatible)

Leave your laptop home and make your presentation from your mobile device. Casio Pro models will project from iPhone®.

Android®, iPad®, iPod® and Microsoft Windows® Mobile, via a WiFi 802.11b/g/n connection. Software is required and included with select Casio USB models. Device application is also required and available by free download with select Casio USB models.

AUTOMATIC BRIGHTNESS ADJUSTMENT

Power saving automatic use of ECO mode and proper brightness for reduced eye fatigue.









SPECIFICATIONS | XJ-H2650

Drinktores	'	3500 lumana
Brightness Contrast Ratio	Telephoto Mode	3500 lumens 1400 : 1
Zoom	relephoto Mode	1.2X Manual
Focus		Manual Focus
Lens Offset		100%
Light Source		Casio Laser & LED Hybrid
Estimated Operating Life		Up to 20,000 Hours (Warranty 3 years or 6,000 Hrs)
Projection Screen Size	70°-1	27 ~ 300-inch diagonal
Projection Range	60-inch screen	TBD
	100-inch screen	TBD
	Minimum	TBD
Projection System	Projection Ratio	TBD
		DLP®
	Device Type	0.7-inch DLP Chip
	Native Resolution	1280 x 800
	Native Aspect Ratio	16:10
Color Reproduction		Full Color (16.77 Million Colors)
Keystone Correction		Vertical +30° (Auto) Vertical + or - 30° (Manual)
Dimension	Including Projections	15.75 x 12.72 x 4.17 Inches
	Excluding Projections	15.75 x 12.72 x 3.78 Inches
Weight		15.6 lbs
Power Source		AC100~240V, 50/60Hz
Power Consumption	Operating	Operating power: 350W (with Eco Mode "Eco 1" selected),
		430W (with Eco Mode Off "Bright" selected)
	Standby	0.4 w (LAN OFF), 4.8 w (LAN ON)
Security Compatibility	Kensington Compatible	Yes
	Power On Password	Yes
Ceiling Mount		Mount optional and available separately from 3rd party vendors
Mounting Screw Size		
and Quantity		M4 Qty. 4 (Optional and sold separately)
Manufactured in		China
OTHER INFORMATION		
		44.000
Usage Environment	Operating Temperature	41~95°F
	Operating Humidity	20~80% (non condensation)
	High Altitude Mode	Yes (For Operation 3,300~6,600 ft)
Remote Control Range		16.5 ft Maximum
Limited Warranty		3 years Parts and Labor Plus 3 Years or 6,000 hours
		light source, see Warranty Statement included with
		product for complete details
Included Accessories		Wireless remote control, 6' RGB cable, 6' AV cable, 6' AC Power Cord,
		Manual on CD-ROM and booklet, Wireless LAN Adapter (YW-3)
Included Software	Windows® Compatible Only	Windows® Only—Wireless Connection 3/EZ-Converter
		FA/ArcSoft Media Converter 3 For CASIO Projector
		(ONLY USB MODEL)
Optional Accessories		Active Shutter 3D Glasses (YA-G30)/ 2D-3D Conversion
		Software (YA-D30)/Interactive (IWB) Pen (YA-P10)
I/O CONNECTIVITY		
		mini D Sub 15 min v 2 Alex use as VCb CoVDb Du insust
RGB/Component Video Input		mini D-Sub 15 pin x 2 Also use as YCbCr/YPbPr input—
March Barrier		commercially available adapter required
Native Resolution		(1024 x 768) 786,432 pixels
Digital Input		HDMI Type A x 1 (Locking Type)
RGB Output		Mini D sub 15 pin x 1
Audio	Input	RCA (R/L) x1, Stereo mini x 2
	Output	Stereo Mini x 1
	Speaker	10W Monaural Speaker
Video Signal Compatability	Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
	DTV/HDTV	480i/480P/576i/576P/720p/1080i/1080p
Video Input		Composite Video (RCA) x 1, S-Video x 1
Control Terminal		RS-232C (Mini D sub 9 pin) x 1
USB		
		RS-232C (Mini D sub 9 pin) x 1 Type A (USB 2.0) x 1, Type B x 1 RJ-45 x 1
USB	Connectable Equipment	Type A (USB 2.0) x 1, Type B x 1
USB	Connectable Equipment	Type A (USB 2.0) \times 1, Type B \times 1 RJ-45 \times 1 USB memory (commercially available) (Not Included)
USB	Connectable Equipment	Type A (USB 2.0) x 1, Type B x 1 RJ-45 x 1





Wireless LAN Adapter (YW-3) is included with USB Models

(802.11 b/g/n)

Wireless Capability