

Dell 1610HD Value Series Projector

PROJECTION

Brightness:

3000 ANSI Lumens (Max.)

Contrast Ratio:

2100:1 Typical (Full On / Full Off)

Resolution:

WXGA (1280 x 800)

Uniformity:

85% Typical (Japan Standard - JBMA)

Projection Lens:

F-Stop: F/2.4~2.66

Image Size:

36.3" ~ 362" (diagonal)

Projection Distance:

1.2m ~ 10m

Set Up:

3D - Enabled

CONNECTIVITY

Power: AC power input socket

Computer Input: two D-sub for analog/RGB component, HDTV input signals

Computer Output: one 15-pin D-sub

Video Input: one composite video RCA and one S-video

USB Input: one USB slave for remote support and firmware upgrade

Audio input: one phone jack (Diameter 3.5mm) and one pair of RCA connector; one microphone input

HDMI Input: one HDMI 1.3 (HDCP compliant)

RS232: One mini-DIN RS232 for wired remote projector control from PC

LAMP

Lamp Life Cycle³:

Up to 3000-hour Typical

Up to 4000-hour Eco-Mode

Lamp Type:

Philips E20.9 225W

VIDEO COMPATIBILITY

S-Video/Composite Video: NTSC [J, M, 4.43, supports Closed Captioning

(CC1~CC4)], PAL (B, D, G, H, I, M, N, Nc, 60), SECAM (B, D, G, K, K1, L)

Component Video (via VGA) & HDMI (HDCP Compliant) - 480i/p, 576i/p, 720p, 1080i/p PC (VGA, HDMI): Refer to 3.10 Computer Compatibility Modes

AUDIO

Multimedia Audio:8W Speaker

KEYSTONE CORRECTION

Vertical: +40° / -35°

Horizontal: N/A

COLOR, SIZE AND WEIGHT

Dimensions (W x D x H):

11.68" x 7.96" x 3.46"(296.5 x 202 x 87.9mm ± 1mm)

Weight:

5.2 lbs (2.36kg)

Environmental and Regulatory
ELECTRICAL

Power:

Universal AC 100-240 50-60Hz with PFC input

Power Consumption Operational:

Normal mode: 287W +/-10%

@110Vac(Network On); 275W +/-10%

@220Vac(Network On)

Eco mode: 219W +/-10%

@110Vac(Network On); 212W +/-10%

@220Vac(Network On)

Power saving mode: less than 15W

(Network On, fan speed at minimum)

Standby mode: less than 1W (Network Off & VGA_OUT off)

ENVIRONMENTAL

Operating temperature:

5°C - 35°C (41°F - 95°F)

Humidity:

80% (maximum)

Storage temperature:

0°C - 60°C (32°F - 140°F)

Humidity:

90% (maximum)

Shipping Temperature:

-20°C - 60°C (-4°F - 140°F)

Humidity:

90% (maximum)