

PGWU-61B

5,900 lumens, WUXGA, single-chip DLP Present projector



WUXGA
1920x1200

6K
LUMENS

1-CHIP
DLP™

This eye-catching white projector will fit perfectly with your modern meeting room or boardroom and enables you to do your business without worrying about the technology.

Why you'll love the Present range

- **Stylish design** that seamlessly blends in with your office interior
- **High-quality images** with an unmatched level of detail and contrast
- **Button-free and cable-free** for simple operation and less clutter
- **Reliable DLP technology** for true ease of mind
- **Easily upgradable** with future connectivity add-ons
- **Low cost of ownership** thanks to DLP technology and sealed optics
- Preset image modes that allow for **flexible color management**
- **Intuitive control menu** with the most common features at your fingertips
- **User-friendly remote control** that features just one button

BARCO

Visibly yours

Technical specifications**PGWU-61B**

| | |
|---|--|
| Projector type | WUXGA single-chip DLP projector |
| Technology | 0.67" DMD |
| Color wheel | 6S standard (RGBYCW) |
| Resolution | 1,920 x 1,200 WUXGA |
| Brightness | 5,900 ANSI lumens* 4,250 ANSI lumens (eco-mode)* *Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. |
| Contrast ratio | 1,100:1 / 4,800:1 (dynamic contrast mode) |
| Brightness uniformity | 85% |
| Aspect Ratio | 16:10 |
| Lens type | G lens |
| Lenses | 1.22-1.53:1; 0.95-1.22:1; 1.52-2.92:1 |
| Optical lens shift | Vertical: -100% to +100% / horizontal: -28% to +28% |
| Color correction | CCN (for 1 chip) |
| Lamps | 1 x 465W Ushio |
| Lamp lifetime | Up to 1,500 hours (full power) / Up to 2,000 hours (eco mode) |
| Transport with lamp | Yes |
| Sealed DLP™ core | Sealing between TIR prism and DMD |
| Advance Picture in Picture | Yes |
| Orientation | table - ceiling |
| Keystone correction | Yes |
| Inputs | G/Y, B/Pb, R/Pr, H/C, V; VGA; CVBS; HDMI-1 v1.3 ; DVI-D |
| Input Resolutions | up to WUXGA (1,920 x 1,200) 60Hz |
| Software tools | Projector Toolset |
| Control | IR, RS232, RJ45 |
| Network connection | 10/100 base-T, RJ-45 connection |
| Power requirements | 100-240V / 50-60Hz |
| Max. power consumption | 585W @ 110V/540W @ 220V 470W @ 100VAC/460W @ 240VAC (eco mode) / less than 0.5W (standby) |
| Noise level (typical at 25°C/77°F) | Typical 40 dBA (bright mode) / Typical 37 dBA (eco mode) |
| Operational ambient temperature | 5-40°C / 41°-104°F (sea level) |
| Operational humidity | 10-85% |
| Dimensions (WxLxH) | 475 x 565 x 253.6mm |
| Weight | 17 kg |
| Shipping dimensions (WxLxH) | 934 x 574 x 440 mm |
| Shipping Weight from Factory | 23 kg |
| Certifications | CB test certificate, US emc, US safety, CE emc and safety, CCC emc and safety |
| Warranty | 3 years standard warranty** **Warranty and service conditions can differ from region to region. Contact your local sales or service rep for more details |

Generated on: 06 Dec 2013
Technical specifications are subject to change without prior notice.
Please check www.barco.com for the latest information.

BARCO

Visibly yours