

High performance LCD projector captures attention in classrooms or conference rooms with dynamic images and 2,500 ANSI lumens.



Key Features

- WXGA 1280 x 800 resolution
- 2,500 ANSI lumens white/color output
- 16 watt audio output
- 3000:1 contrast ratio
- HDMI 1 input
- 5,000 hours hybrid filter*
- 5,000 hours lamp life (Standard mode) and 6,000 hours lamp life (Eco mode)**
- Power saving standby mode less than .5W



From the classroom to the conference room, Hitachi's CP-WX2515WN LCD projector combines superior image clarity, high quality value, and long-life reliability. Bright, vivid colors with razor-sharp text and bold graphics will truly enhance any lesson or meeting and make it more memorable. Further engage the audience by annotating over images with the optional TB-1 tablet and pen. For greater installation convenience, the CP-WX2515WN has a cloning function which enables you to copy setting data from one projector to others of the same model via USB memory. Plus, Hitachi's Intelligent Eco Mode with ImageCare combines optimal picture performance with maximum energy savings for a lower total cost of ownership. For added peace of mind, Hitachi's CP-WX2515WN is also backed by a generous warranty and our world-class service and support programs.

CP-WX2515WN

UNIQUE FEATURES

Drawing Function with Optional Tablet (TB-1)



The optional Hitachi wireless tablet and pen allows you to engage your audience by annotating over images shown on the projector.

Cloning Function



Copy setting data from one projector to others of the same model via USB memory. Cloning can save almost all PJ settings such as gamma and keystone via USB memory.

ImageCare Technology



ImageCare is a lamp power control function that combines optimal picture performance with maximum energy savings by decreasing energy usage, improving contrast ratio and lengthening lamp life. The result is a lower total cost of ownership and decreased maintenance cost.

Intelligent Eco and Saver Modes



Automatically changes the brightness of the lamp if there is no change in the screen image. Using ImageCare technology, this feature gives optimal picture performance with maximum energy savings and can increase lamp life and lower total cost of ownership.

STANDARD FEATURES

Display via USB



Simply plug and play using the USB port instead of the 15-pin D-sub VGA cable.

Input Source Naming



Users can name input sources in simple language instead of factory default name. **Exclusive to Hitachi.**

Microphone Input



A microphone can be used via the jack located on the input panel. Allows for more dynamic presentations even in standby mode.

Network Control, Maintenance and Security



Embedded networking gives you the ability to manage and control multiple projectors over your LAN. Features include scheduling of events, centralized reporting, image transfer and e-mail alerts for reactive and routine maintenance.

PC-Less Presentation



By using a USB memory stick or other storage device, you can use the projector without a computer. Menus are easy to see with a thumbnail display. Additionally there is also a slideshow function.



PIN Lock / MyScreen / MyText



PIN lock protection can limit projector users. MyScreen PIN lock keeps captured images on the startup screen. Users can set any name logo to MyScreen, clearly identifying ownership. MyText provides the ability to write text on the startup screen such as model name, serial number or location.

PJMessenger



PJMessenger function allows you to send and display text messages and audio alerts on your networked projectors. It is an easy and efficient way to send announcements out to multiple units.

Present Content via LAN



Hitachi's suite of networking software allows you to easily send content directly from your PC to the projector via your LAN connection.

Serial Number and Media Access Control Label



A label is affixed to side of projector to more easily access and read the model name, serial number and MAC address while mounted in ceiling use. This is a convenience for installers, end users and auditors for instant accessibility.

Wireless Presentation Ready



You can use a wireless network by connecting the projector to a computer using the optional USB wireless adapter part number USBWL11N. The adapter supports IEEE802.11b/g and the latest 11n.

CP-WX2515WN LCD Projector

HITACHI
Inspire the Next

Long-life reliability with a lower total cost of ownership.

From classrooms to conference rooms, Hitachi's CP-WX2515WN can make a big impact on your audience. With 2,500 ANSI lumens brightness and WXGA 1280 x 800 resolution, the CP-WX2515WN is designed to make any message more memorable with colorful images, crisp text, and powerfully



clear audio. Incorporating Hitachi's leading-edge technology, the CP-WX2515WN features high contrast ratio, long lamp life, cloning function enabling you to copy settings data from one projector to others of the same model, and is wireless presentation ready. Plus, embedded networking gives you the ability to manage and control multiple projectors over your LAN (scheduling of events, centralized reporting, image transfer, and e-mail alerts). Even with the the array of advanced features, Hitachi's CP-WX2515WN is designed for user-friendly operation and installation convenience.



Front View



Top View




Left Profile



Right Profile

Input/Outputs



- | | | |
|-------------------|--------------------|-----------------------|
| 1. USB Type A x 2 | 7. Audio in 1 | 13. Microphone Input |
| 2. USB Type B | 8. Audio in 2 | 14. Control (RS-232C) |
| 3. HDMI | 9. Composite Video | 15. Kensington Lock |
| 4. Computer in 1 | 10. S-Video | 16. Security Bar |
| 5. Computer in 2 | 11. Audio Out | 17. LAN |
| 6. Audio In 3 | 12. Monitor Out | |



3LCD Technology



Closed Captioning



Crestron Integrated Partner



AMX Device Discovery



Hitachi Trade-Up Program



3 Year Warranty

HDMI HDMI

HI0045-05/12 WEB
All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2012 Hitachi America, Ltd. All Rights Reserved.

Hitachi America, Ltd.

900 Hitachi Way, Chula Vista, CA 91914
Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com
Web: hitachi-america.us/projectors

CP-WX2515WN



CP-WX2515WN LCD Projector

HITACHI
Inspire the Next



Accessories and Lenses	
Supplied Accessories	Remote control, power cord, computer cable, network and wireless software, user's manuals, safety manual
Optional Accessories	USBWL11N USB wireless adapter, TB-1 wireless USB tablet
Optional Lenses	NA
Replacement Parts	
Lamp	CPX2015WNLAMP (DT01371) with filter
Remote Control	HL02881
Filter	MU06481

Projection Throw Chart

Screen Size 16:10		Throw Distance	
Diagonal	Width	Min	Max
30	25	35	43
60	51	73	89
80	68	99	121
100	85	125	152
150	127	190	229
200	170	254	307
300	254	383	463

Throw Ratio: 1.5 - 1.8 : 1 (distance : width)
Screen size and throw distance are measured in inches.

Specifications		
Display	Projection Technology	3LCD, 3 chip technology
	Resolution	WXGA - 1280 x 800
	White Light Output	2,500 ANSI lumens
	Color Light Output	2,500 ANSI lumens
	Colors	16.7 million colors
	Aspect Ratio	Native 16:10 and 4:3 / 16:9 compatible
	Contrast Ratio	3000 : 1 (using active IRIS)
Lens & Operation	Throw Ratio (distance : width)	1.5 - 1.8 : 1
	Lens	x1.2 with manual zoom
	Lamp Wattage	215W UHP
	Expected Lamp Life*	Approximately 5,000 hours (standard mode) 6,000 hours (Eco mode)
	Expected Filter Life**	Approximately 5,000 hours
	Speaker Output	16W (8W x 2)
	Acoustic Noise Level	36 dB (29 dB in Eco mode)
Compatibility	Keystone	+/- 30° vertical only
	Computer	VGA, XGA, WXGA, WXGA+, SVGA, SXGA+, UXGA (compressed), MAC 16"
	H-Sync	31.5 kHz - 106 kHz
	V-Sync	56 Hz - 120 Hz
	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p
	HDMI	480i, 480p, 576i, 720p, 1080i, 1080p, Computer signal TMDS Clock 27 MHz - 150 MHz
Connectors	Digital Input	HDMI x 1 (HDCP compliant)
	Computer Input 1	15-pin mini D-sub x 1
	Computer Input 2	15-pin mini D-sub x 1
	Computer Monitor Output	15-pin mini D-sub x 1
	Video Input	
	S-Video	Mini DIN 4-pin x 1
	Composite Video	RCA jack x 1
	Component Video	15-pin mini D-sub x 2 (shared w/analog computer 1/2)
	Audio Input	3.5 mm stereo mini jack x 2, RCA jack (L/R) x 1
	Audio Output	RCA jack (L/R) x 1
	Network LAN Wired	RJ-45 port / 100-base-T
Network LAN Wireless	IEEE802.11 b/g/n - optional wireless adapter required	
Ratings & Warranty	USB	Type A x 2 (PC-less, wireless adapter, TB-1) Type B x 1 (USB display or mouse control)
	Control Terminals	9-pin D-sub x 1 (RS-232 control)
	Power Supply	AC90-132V / AC198-264V, 50/60Hz
	Power Consumption	310W
	Operating Temperature	40°F - 95°F (5°C - 35°C)
	Dimensions (W x D x H)	12.5" x 11.3" x 3.9"
	Weight	8.15 lbs.
Approvals	UL 60950-1 / cUL FCC Part 15 subpart B class B	
Warranty	3 year limited parts and labor	

* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.

** Actual filter life will vary by individual filter and based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty.

CP-WX2515WN

HI0045-05/12 WEB
All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation.
©2012 Hitachi America, Ltd. All Rights Reserved.

Hitachi America, Ltd.
900 Hitachi Way, Chula Vista, CA 91914
Toll Free: 1.800.HITACHI • Email: dmd.info@hal.hitachi.com
Web: hitachi-america.us/projectors

