

WUXGA Professional Installation Laser Projector

ZU1050

Spectacular image quality and brightness with low maintenance laser technology



PRO | SCENE

- Sharp and luminous image with 10,000 lumens
- DuraCore: maintenance-free laser light source at full brightness up to 20,000 hours
- MultiColor Laser technology provides a wider color gamut with high brightness
- Integrated edge-blending and image warping with portrait and 360° operation
- Robust connectivity, including HDMI, HDBaseT, 3G-SDI and wireless mirroring via USB adapter
- Multiple interchangeable optical lens options with 24/7, 360° and portrait mode operation



The Optoma ZU1050 is a professional installation 10,000 lumen WUXGA projector designed for large meeting rooms, auditoriums, museums, houses of worship and broadcast environments demanding vibrant colors, consistent brightness and stunning quality. Laser phosphor technology delivers powerful brightness with up to 20,000 hours of operation.

It's engineered to suit complex installation requirements for professional image projection. The dust-sealed and filter-free design with IP6X certification keeps the optical system performing optimally with minimal maintenance. A variety of premium lens options, motorized lens-shift, zoom and focus with 360° and portrait operation ensure installation flexibility for virtually all needs.

CONNECTIVITY (May require optional accessories)



Computers



Smart Phones



Tablets




3D Blu-ray/DVD Players



Broadcasting Camera



Apple TV®



Chromecast™

WUXGA PROFESSIONAL INSTALLATION LASER PROJECTOR – ZU1050

OPTICAL/TECHNICAL SPECIFICATIONS

Display Technology	Single DMD, 0.67" WUXGA DMD, Type A, DC3 DLP® Technology by Texas Instruments™
Native Resolution	WUXGA (1920x1200)
Maximum Resolution	WUXGA (1920x1200)
Brightness	10,000 ANSI lumens, 10,000 center lumens
Contrast Ratio	2,000,000:1 (Extreme black enabled) 2000:1 (full on/full off) (Dynamic Black)
Lamp Life and Type*	Up to 20,000 hrs
Lens Options:	BX-CTA16: 0.36:1 BX-CTA15: 0.75-0.95:1 BX-CAA01: 0.95-1.22:1 BX-CAA06: 1.22-1.52:1 BX-CAA03: 1.52-2.92:1 BX-CTA13: 2.90-5.50:1 BX-CTADOME: Dome projection
Projection Method	Front, rear, ceiling mount, table top, 360° and portrait mode operation capable
Geometric Correction	±20° vertical and horizontal keystone, 4 corner, pincushion/barrel
Lens Shift	±50% vertical ±15% horizontal
Uniformity	90%
Aspect Ratio	16:10 (native), 16:9 and 4:3 compatible
Throw Ratio	0.36 - 5.50 (dependent on installed lens)
Projection Distance	2'6" - 116'4" (0.81 - 35.5m)
Image Size	50" - 300"
Projection Lens	Interchangeable lenses (lens not included)
Optical Zoom	1.25x - 1.9x (dependent on installed lens)
Digital Zoom	0.8 - 2.0
Audio	NA
Noise Level	35dB/37dB (typical/max)
Remote Control	Full function wired remote
Operating Temperature	41–104°F (5–40°C), 85% max humidity
Power Supply	AC input 100 – 240V, 50–60 Hz
Power Consumption	945W+/-15% Max (Bright), 480W+/-15% Max (ECO) @ 110V AC
High Altitude	Must manually switch to high altitude mode @ 5000 feet & above (using OSD)

COMPATIBILITY SPECIFICATIONS

Computer Compatibility	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Mac compatible
Video Input Compatibility	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
3D Compatibility[†]	Supports all HDMI 1.4a mandatory 3D formats (frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz (i.e. 60 or 72 frames per eye). Required 3D glasses are sold separately. Refer to user manual for details.
Vertical Scan Rate	24–85Hz, 120Hz
Horizontal Scan Rate	15.375–91.146KHz
User Controls	Complete on-screen menu adjustment in 12 languages
I/O Connection Ports	1 x HDMI-in (version 1.4), 1 x DVI-D, 1 x VGA-in (D-Sub 15pin) (computer in or component), 1 x HDBaseT, 1 x 3G-SDI, 1 x 3D SYNC In, 1x VGA-out (supports VGA passthrough to monitor) (monitor out), 1 x 3D SYNC out, 1 x HDMI-out (version 1.4), 1 x RS232 (D-sub 9 pin) (PC Control), 1 x wired in (3.5mm phone jack) (remote in), 1 x USB Type A (for Wi-Fi adapter), 1 x mini USB (service), 1 x RJ45 (LAN)

PHYSICAL SPECIFICATIONS


Security	Kensington® Lock port, security bar and keypad lock
Weight	50.7 lbs (w/out lens)
Dimensions (W x H x D)	19" x 7.7" x 20.7" (482 x 195 x 525 - with elevators)

*Light source life is dependent upon many factors, including brightness mode, display mode, usage, environmental conditions and more. Light source brightness can decrease over time.

[†]3D content can be viewed with DLP Link active shutter 3D glasses when projector is used with a compatible 3D player. Please visit www.OptomaUSA.com for more information.



- | | | |
|------------------------|----------------|------------------|
| 1. Power On/Off | 7. HDMI Out | 13. Wired Remote |
| 2. Menu Navigation Pad | 8. HDMI In | 14. 3D SYNC In |
| 3. 3G-SDI | 9. 3D SYNC Out | 15. USB Power |
| 4. DVI-D | 10. HDBaseT | 16. Service |
| 5. VGA-In (YPbPr) | 11. RJ-45 | 17. AC Power |
| 6. VGA-out | 12. RS-232C | 18. Power Switch |



Warranty

3-year or 20,000 hour light source warranty (whichever comes first), 3-year Optoma Express advance exchange warranty on the projector.

What's in the Box

ZU1050 projector, AC power cord, VGA cable, remote control, batteries for remote, multilingual CD-ROM user's manual, quick start card, and warranty card

Optional Accessories

Universal ceiling mount, DLP@Link™ 3D glasses, wireless adapter, remote, HDBaseT transmitter

Accessory Part Numbers

Ceiling mount: BM-9011N
Remote: BR-3074W
DLP@Link™ 3D glasses: ZD302
Wireless: WUSB-PRO
HDBaseT transmitter: 4K100TX

UPC 796435 44 147 0

www.OptomaUSA.com

