

### LampFree. MercuryFree. StressFree.

The Casio Advanced Series is the next generation in LampFree. Advanced Series Projectors provide high brightness, up to 3500 ANSI lumens in XGA and WXGA resolutions. Two (2) HDMI inputs provide connectivity with all current display technology without the need for switching cables. A high power USB port (DC 5V 2A) provides direct power for USB stick devices and eliminates the need for a separate power supply. All Casio LampFree Projectors are built to last and backed by an "Industry best" 3 year parts and labor warranty plus 5 years or 10,000 hours on the light source out of the box.

Network ready models incorporate LAN Connectivity (RJ-45) plus a USB port for PC-Less presentations (USB Thumb drive) and are WiFi ready.

#### Key Features

- Two (2) HDMI inputs
- Power USB port (DC 5V 2A)
- Dust resistant design
- Instant Light Control 7 level
- High Power 16 watt speaker
- 1.5 X Manual Zoom/Focus Lens
- DLP® Technology

#### LampFree Features

- Laser & LED Light Source
- Long Life, 20,000 hour estimated operating life
- No Lamp replacement required
- No Down Time
- Low Power Consumption
- Mercury Free
- Instant On (5 seconds to full brightness)
- Instant Off no cool down required

#### Terminal Interface



# XJ-F20XN

## **ADVANCED SERIES**

CASIO Projector Specifications	ADVANCED SERIES XJ-F20XN
	XGA
Native Decelution	
Native Resolution	1024 x 768
Native Aspect Ratio	4:3
Brightness	3300 lumens
Display Device	0.55 -inch DLP® chip
Contrast Ratio	20,000:1
_ens Type	1.5X Manual Zoom & Focus
ens Offset	50%
.ight Source	Laser & LED
Estimated Light Source Life	Up to 20,000 Hours
icreen Size (Min-Max)	30 to 300-inch diagonal
rojection Range	So to Soo-Incir diagonal
	(4.045
60-inch screen	6.4 ~ 9.4 ft
100-inch screen	10.9 ~ 15.9 ft
Minimum Throw Distance	3.1 ft
Throw Ratio	1.66-2.42:1
Reystone Correction	Vertical +30° (Auto) Vertical + or - 30° (Manual)
Color Reproduction	Full color (up to 1.07 billion colors)
owerSource	AC100~240V, 50/60Hz
ower Consumption	
	195 W - light control "off" Bright selected
Operating	160 W - light control "on" and "Light Output 7" selected
Standby	0.12 W (Remode On : Disable), 1.9 W (Remote On : Enable)
ERMINAL CONNECTIVITY	
'ideo Signal Compatibility	
Video Systems	NTSC/ PAL/ PAL-N/ PAL-M/ PAL60/ SECAM
DTV/HDTV	480i/480p/576i/576p/720p/1080i/1080p
Maximum Computer Input	WUXGA (1920 x 1200) *Reduced blanking signal
NPUTS	
RGB/Component Video Input	mini D-Sub 15 pin x 1 (Also use as YCbCr/YPbPr input— commercially
KGB/Component video input	available adapter required)
IDMI	HDMI Type A x 2, HDCP and audio support
Composite Video	Composite Video (RCA) x 1, S-Video x 1
Audio	RCA (R/L) x 1, 3.5mm stereo mini jack x 1
JSB Power Supply	Yes, DC 5V 2A
	USB Type A x 1 shared with DC 5V 2A
JSB Input (Host)	<i>1</i> 1
JSB Display	USB Type B x 1
_ogo Transfer	Micro B(USB1.1) x1
Built-in Memory	Yes, Approximately 2GB
Wireless Capability	Optional Wireless LAN Adapter (YW-40)
OUTPUTS	
Audio	3.5mm Stereo Mini Jack x 1 (variable audio)
	S.S.M. Steleo Mini Steleo Mini Steleo
AUDIO AND CONTROL SYSTEMS	
Audio system	16W Monaural Speaker
Control Terminal	_
RS-232	RS-232C (D sub 9 pin) x 1, Cross Cable (Null Modem) required
LAN	RJ-45 x1
Control System Compatibility	AMX, Crestron, Extron
OTHER INFORMATION	
Jsage Environment	—
Operating Temp/Humidity	41~95°F / 20~80% (non condensation)
High Altitude Mode	Yes (for operation 5,000~10,000 ft)
extended operation (24 x 7)	Yes – Note: Projector must be turned off once every 24 hours
lotation Projection	Free Orientation
Closed Captioning	Yes
	16.4 ft Maximum
temote Control Range	
Security Compatibility	Kensington™ Compatible / Power On Password
Ceiling Mountable	Yes, available and sold separately by 3rd party vendors
Ceiling Mount Screws	M4 x 4(not included) Insert Depth 5-8 mm
imited Warranty	3 years Parts and Labor plus 5 years or 10,000 hours light source, see Warranty Statemer
anneed warrancy	included with product for complete details.
	Wireless Remote Control, Batteries (AAA-size×2), AC Power Cord, RGB Cable,
ncluded Accessories	Warranty and Safety Precautions
	Wireless LAN Adapter YW-40, Soft carrying case YB-2
Optional Accessories	
Optional Accessories	White
Dptional Accessories Cabinet Color	
Dptional Accessories Cabinet Color Dimension (W x D x H)	White —
Dptional Accessories Labinet Color Dimension (W x D x H) Including Projections	White 
Dptional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections	White 
Excluding Projections Veight	White 
Dytional Accessories Gabinet Color Dimension (W x D x H) Including Projections Excluding Projections Veight lacking Information	White 
Optional Accessories abinet Color Jimension (W x D x H) Including Projections Excluding Projections Veight	White 
Optional Accessories Tabinet Color Imension (W x D x H) Including Projections Excluding Projections Veight acking Information	White 
Deptional Accessories Cabinet Color Dimension (W x D x H) Including Projections Excluding Projections Veight acking Information Carton Dimensions	White 

© 2016 Casio America, Inc. All rights reserved. Casio is a registered trademark of Casio Computer Co., Ltd. In the United States and/or other countries. Specifications were thought to be correct at time of publication. All specifications and features are subject to change without notice. DLP, the DLP logo and the DLP medallion are trademarks of Texas Instruments. XGA is a registered trademark of International Business Machines Corporation in the United States. HDMI is a trademark or registered trademark of HDMI Licensing, LLC. Other product names or company names on this specification brochure are either trademarks or registered trademarks of their respective owners.

Designed and Manufactured by Casio in Japan TAA Compliant

CASIO. 570 Mt. Pleasant Avenue, Dover, New Jersey 07801 TEL 973-361-5400 FAX 973-537-8979

www.casioLampFree.com PJ-059-01

LampFree.