IN134



The Superpowered Projector Designed for Use with Google Chromecast and Other Devices Part #: IN134

The InFocus IN134 XGA projector combines stellar image performance, long-life lamp and low cost with the ability to create a more powerful and dynamic education experience. Simply insert your Google ChromeCast, Intel Computer Stick, Android solution, or other device into the projector's TechStation internal HDMI 1.4 bay and turn your projector into an all-in-one classroom solution.

### **Key Features**

- ♦ XGA (1024 x 768) resolution
- TechStation lets you customize your projector with the devices you already use
- Powered HDMI for mobile charging and device power
- 28,500:1 contrast ratio and up to 4000 lumens for depth of image and life-like colors
- Long life lamp of up to 15,000 hours
- Class-leading, whisper-quiet design















# Customize your projector using TechStation

With an HDMI port and multiple ways to connect your devices, the TechStation superpowers your projector and enables more effective learning by working seamlessly with the tools you already use. After connecting your device, close up the TechStation's lid to create a streamlined, all-in-one solution for streaming audio and video.

IN130 Series projectors work with:

- Google ChromeCast Ultra
- Intel Computer Stick
- Asus Chromebit
- Amazon Fire TV Stick
- Android stick

 And more HDMI-supported devices to enable casting, streaming, and wireless



when not in use, and save even more money over the life of the projector.

#### Over 1 Billion Colors

BrilliantColor™ DLP imaging technology lets images shine with over 1 billion colors that ensure life-like color accuracy and eyecatching presentations. Get better, brighter images on whiteboards, blackboards, or beige walls, in any light.

### Engage Audiences from Every Angle with 3D

Bring content to life with support for multiple forms of 3D -- including Blu-Ray, 3D broadcasting, videos games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately).

# Quietest Projector in its Class

Make sure students always hear the lessons, not the fans. With only 21dB in eco mode, IN134 projector was designed to be quieter, with Smooth Flow fan technology, a cooling-efficient enclosure, and silent bearings.



## Save Energy with Value that Lasts

IN130 projectors are designed to fit your budget go the distance with ultra-long lamp life of up to 15,000 hours and no filters to clean or replace. Unlike other imaging technologies, the TI DLP® chip ensures no image decay over time so your projector lasts longer. Activate Dynamic Mode to dim the image

### Easy to Install and Manage

Quickly and simply install and manage your projector over your school's network with free <u>ProjectorNet 4.1 software</u> from InFocus, or choose to utilize Crestron Roomview or AMX Device Discovery.

### Specifications\*

Projector	IN134
Resolution – Native	XGA (1024 x 768)
Display Technology	DLP
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Speakers	Mono 10W x 1
Lamp Brightness	4,000 lumens
Lamp Brightness – Eco Mode	3,200 lumens
Lamp Life	5,500 hours
Lamp Life – Low Power	10,000 hours
Lamp Life - Dynamic Mode	15,000 hours
Lamp Power	220W

Lump New — Exe Mode         M5W           Color Wheel         Migh Speed 6 Segment RYGCWB           Number of Calors         107 billion           Synch Scan Frequency — Horizontal         315 * 976 kHz           Synch Scan Frequency — Vertical         45           Appect Ratio Compatibility         169, 1600, 2,351, 11, 21, 139, 159, 54           Projection Lans F Stop — Minimum         2,31           Lans Yape         Manual facus           Image Size — Maximum         2,41           Lans Yape         Manual facus           Image Size — Maximum         2,41 in           Projection Lans F Stop Maximum         2,41 in           Lans Yape         Manual facus           Image Size — Maximum         2,44 in           Projection Offset         1,55 + 58 W           Keystone Correction         4,00 W           Connectors – Dutputs         3,5 mm audio, Composete video, WGA, HDMI 14a x3 (with 14a x30 support), USB-A [TeckStation Connection]           Controll         8,222 IR Rimote           Auchtel Noise Eco Mode         2,1 deA at 0°F / 178°C           Included Accessories         Power cond, Bernote, HDMI Cable, Documentation, User Manual (CD)           Disapport         1800 Ag 50 Hz, All HDMI Lak 30 formats, DLP Link 30 glasses required           Power Consumption — S	Projector	IN134
Color         Might Speed & Segment RYGCWB           Number of Colors         107 billion           Synch Scan Frequency - Horizontal         31.5 "978 kHz           Synch Scan Frequency - Vertical         56 120 kHz           Aspect Ratio Compatibility         169, 1610, 2351, 11, 21, 313, 159, 54           Projection Lens F-Stop - Minimum         2.53           Len's Type         Manual focis           Image Size - Minimum         2.44           Image Size - Minimum         2.44 in           Projection Order         1.55 + 25 V           Keyston Correction         4.40V           Connectors - Inputs         3.5mm audio comput. Monitor out (VGA)           Connectors - Outputs         3.5mm audio comput. Monitor out (VGA)           Control         85.23, IR Remate           Audible Note - Eco Made         2.1 disk at 67 + 7.176°           Included Accessories         Power Consumption         3.00,000 max           Power Consumption - Eco Mode         2.1 disk at 67 + 7.176°         1.0 list of Accessories           Power Consumption - Eco Mode         2.1 disk at 67 + 7.176°         1.0 list of Accessories           Power Consumption - Eco Mode         2.1 disk at 67 + 7.176°         1.0 list of Accessories           Power Consumption - Eco Mode         2.2 disk at 67 + 7.176°         <	Lamp Power – Eco Mode	145W
Number of Colors         1.07 billion           Synch Sean Frequency - Horizontal         31.5 "976 RHz           Synch Sean Frequency - Vertical         56 - 120 kHz           Aspect Ratio         4.3           Aspect Ratio Compatibility         16.9 (16.0) 2.35.1, 13.21, 13.9, 15.9, 5.4           Projection Lens FStop - Minimum         2.51           Lors Type         Manual focus           Image Size - Minimum         2.2 in           Image Size - Moximum         2.4 in           Projection Offset         4.0 V           Connectors - Dutputs         3.5 mm audio, Composite video, VGA, HDM1 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)           Connectors - Dutputs         3.5 mm audio, Composite video, VGA, HDM1 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)           Connectors - Dutputs         3.5 mm audio, Composite video, VGA, HDM1 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)           Control         8.5232, IR Rema           Audible Noise - Eco Mode         < 2.1 dBA of VF / 1/8°C	Contrast Ratio	28,500:1
Synch Scan Freeuency - Horizontal         31.5 ° 97.6 KHz           Synch Scan Freeuency - Vertral         56 - 120 KHz           Aspert Ratin         43           Aspert Ratin Compatibility         169,1 151,0 2,51,1,1,2,1,139,159,54           Projection Lens F-Stop - Maximum         2.53           Lens Type         Manual focus           Image Size - Maximum         2.2 in           Image Size - Maximum         2.44 in           Projection Offset         155 + 55 V           Keystone Correction         4.07 V           Connectors - Ingust         3.5mm audio corpat, Monitor out (VGA)           Connectors - Outputs         3.5mm audio corpat, Monitor out (VGA)           Contrail         RS232; IR Remote           Auchible Noise - Eco Mode         < 21 disk at 0°F / 178°C	Color Wheel	High Speed 6 Segment RYGCWB
Synch San Frequency - Vertical         56 - 120 KHz           Aspect Ratio         43           Aspect Ratio Compatibility         16.9, 16:10, 2.351, 11, 21, 13.9, 15.9, 54           Projection Lean F-Stop - Minimum         2.41           Projection Lean F-Stop - Minimum         2.43           Lans Type         Manual focus           Inange Size - Minimum         2.44 in           Projection Diffset         115% + 5% KV           Keystone Correction         4.40 V           Connectors - Inputs         3.5mm audio composite video, VGA, HDM1.4a x3 (with 1.4a 30 support), USB-A (TechStation Connection)           Connectors - Outputs         3.5mm audio cottout, Monitor out (VGA)           Connectors - Eco Mode         < 21 cl84 at 0°F / 7/8°C	Number of Colors	1.07 billion
Aspect Ratio         4.3           Aspect Ratio         Campatibility         16:9, 16:10, 2:35:1, 1:1, 2:1, 13:9, 15:9, 5:4           Projection Lans F-Stop – Minimum         2.53           Linary Syze         Manual focus           Image Size – Maximum         22 in           Image Size – Maximum         244 in           Projection Offset         115% + 5% V           Keyston Correction         = 40V           Connectors – Inputs         3.5mm audio composite video, VGA, HDMI 1:4a x3 (with 1:4a 3D support), USB A (TechStation Connection)           Connectors – Outputs         3.5mm audio output, Monifor out (VGA)           Control         85232, IR Remote           Control         85232, IR Remote           Included Accessories         Power Consumption           Do Support         10800 @ 66 OHZ, All HDMI 1:4a 3D formats, DLP Link 3D glasses required           Power Consumption – Standby Mode         1.8W max           Power Consumption – Standby Mode         1.8W max           Power Consumption – Eco Mode         2.70 DW max           Power Standard         AC 100 to 2400, 50/60	Synch Scan Frequency – Horizontal	31.5 ~ 97.6 KHz
Aspect Ratio Compatibility         16.9, 16:10, 2.351, 11, 2:1, 13.9, 15:9, 5:4           Projection Lens F-Stop – Minimum         2.41           Projection Lens F-Stop – Maximum         2.53           Lens Type         Manual focus           Image Size – Minimum         2.41           Projection Offset         115% + 5% %           Keystone Cornection         2.44 in           Connectors – Injusts         3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)           Connectors – Outputs         3.5mm audio output, Monitor out (VGA)           Control         RS-322, IR Remote           Audible Noise – Eco Mode         < 2.1 dBA at 0°F / 178°C	Synch Scan Frequency – Vertical	56 - 120 KHz
Projection Lens F-Stop – Minimum         241           Projection Lens F-Stop – Maximum         253           Lens Type — Maximum         22 in           Image Size – Minimum         224 in           Bridge Step – Maximum         244 in           Projection Offset         15% + 5% V           Keystone Correction         1 40°V           Connectors – Inputs         3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 30 support), USB-A (TechStation Connection)           Control         RS 232, IR Remote           Control         RS 232, IR Remote           Audible Noise – Eca Mode         < 21 dBA at 0°F / 1.78°C	Aspect Ratio	4:3
Projection Lens F-Stop – Maximum         25 l           Lens Type         Manual focus           Lens Type         Manual focus           Linage Size – Minimum         22 ln           Linage Size – Maximum         24 ln           Projection Offset         15% + 5% V           Keystone Correction         4 0VV           Connectors – Inputs         3.5mm audio output, Monitor out (VGA)           Control         8.523.2 ik Remote           Audible Noise – Eco Mode         < 21 d BA at 0°F / 178°C           Included Accessories         Power Consumption         Power Consumption           Power Consumption – Standby Mode         1.8W max         Power Consumption – Low Power Standby         0.5W max           Power Consumption – Low Power Standby         0.5W max         Power Consumption – Low Power Standby         0.5W max           Power Consumption – Low Power Standby         0.10 to 2 dOV, 50/60         Power Standby         0.10 to 2 dOV, 50/60           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Kroean, Swedish, Russian, Frinrish, Arabic, Indonesian, Portuguese         Respect Consumption – Consu	Aspect Ratio Compatibility	16:9, 16:10, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4
Lens Type         Manual focus           Inage Size – Minimum         22 in           Inage Size – Maximum         244 in           Projection Offset         115% – 5% V           Kaystone Correction         40°V           Connectors – Inputs         3.5mm audio cutput, Monitor out (VGA)           Control         8.523.2 in Remote           Control         8.523.2 in Remote           Included Accessories         9.0mc cord., Remote, HDMI Cable, Documentation, User Manual (CD)           3D Support         1080.9 @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required           Power Consumption         300.0W max           Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         1.8W max           Power Consumption – Eco Mode         1.8W max           Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         2.0W max           Power Consumption – Eco Mode         2.0W max           Power Consumption – Eco Mode         1.5 to AirC at 0 to 30.0B m           Decamentation Languages         At 10 1047 at 0 to 100000 ft / 5 to 40°C at 0 to 30.0B m           Decamentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Anhaic, Indonesian, Portuguese, Viet	Projection Lens F-Stop – Minimum	2.41
Image Size – Miximum         24 in           Image Size – Miximum         244 in           Projection Offset         115% + 5% V           Keystone Correction         4 40°V           Connectors – Inputs         3.5mm audio cutput, Monitor out (VGA)           Connectors – Outputs         3.5mm audio cutput, Monitor out (VGA)           Connectors – Outputs         3.5mm audio cutput, Monitor out (VGA)           Control         8232, IR Remote           Audible Noise – Eco Mode         21 dBA at 0°F / 17.8°C           Included Accessories         Power Cond. Remote, HDMI Cable, Documentation, User Manual (CD)           30 Support         1080p.@ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required           Power Consumption – Standby Mode         1.8W max           Power Consumption – Standby Mode         1.8W max           Power Consumption – Eco Mode         220.0W max           Power Consumption – Eco Mode         220.0W max           Power Standard         AC 100 to 240V, 50/D0           Operating Conditions         41 to 104°F at 0 to 10000 ft/ 5 to 40°C at 10 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Ardish, India, English, Drainsh, Arabic, Indonesian, Portuguese           Security Features         Kensington tok port	Projection Lens F-Stop – Maximum	2.53
Image Size – Maximum         244 in           Projection Offset         115x + 5x 10 V           Keystone Correction         ± 40°V           Connectors – Inputs         3.5mm audio couput Monitor out (VGA)           Connectors – Outputs         3.5mm audio output Monitor out (VGA)           Control         8523 LR Bemote           Audible Noise – Eco Mode         < 21 dBA at 0°F /-178°C	Lens Type	Manual focus
Projection Offset         115% + 5% V           Keystone Correction         ± 40°V           Connectors – Inputs         3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)           Connectors – Outputs         3.5mm audio output, Monitor out (VGA)           Control         R5232; IR Remote           Audible Noise – Eco Mode         < 21 dBA of Y - / 126°C	Image Size – Minimum	22 in
Keystone Correction         ± 40°V           Connectors – Inputs         3.5mm audio output, Monitor out (VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)           Control         85232, IR Remote           Audible Noise – Eco Mode         < 21 dBA at OT F / 178°C	Image Size – Maximum	244 in
Connectors − Inputs         3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USBA (TechStation Connection)           Connectors − Outputs         3.5mm audio output, Monitor out (VGA)           Control         RS232, IR Remote           Audible Noise − Eco Mode         < 2.1 d8A at 0°F / -17.8°C           Included Accessories         power cond, Remote, HDMI Cable, Documentation, User Manual (CD)           Dower Consumption         300.00 max           Power Consumption − Standby Mode         1.8W max           Power Consumption − Eco Mode         2.00 Vm max           Power Standard         AC 100 to 240V, 50/60           Power Standard         AC 100 to 240V, 50/60           Operating Conditions         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese           Menu Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Hinjinor, Farsi, Japanese, Than           Security Features         Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw Distance – Mainimum         1.94.4           Throw Distance – Mainimum	Projection Offset	115% +- 5% V
Connectors - Outputs         3.5mm audio output, Monitor out (VGA)           Control         RS232, IR Remote           Audible Noise - Eco Mode         < 21 dBA at OF / -17.8°C	Keystone Correction	± 40°V
Control         RS232, IR Remote           Audible Noise – Eco Mode         21 dBA at OF / 178°C           Included Accessories         Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)           30 Support         10800 @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required           Power Consumption Standby Mode         18W max           Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         220.0W max           Power Standard         AC 100 to 2400, 50/60           Operating Conditions         41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Operating Conditions         41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Benu Languages         Finnish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese           Recurity Features         Resington lock port           Security Features         Kensington lock port           TechStation         Workswith Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Aus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw Alzance – Minimum         1 m           Throw Alzance – Maximum         1 g41           Throw Alzance – Maximum         1 g42           Throw Alzance – Maximum <t< td=""><td>Connectors – Inputs</td><td>3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)</td></t<>	Connectors – Inputs	3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection)
Audible Noise – Eco Mode         < 21 dBA at 0°F / -178°C	Connectors – Outputs	3.5mm audio output, Monitor out (VGA)
Included Accessories         Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)           3D Support         1080 p. @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required           Power Consumption         300.0W max           Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         220.0W max           Power Standard         AC 100 to 240V, 50/60           Operating Conditions         41 to 104F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese           Menu Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Plungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai           Security Features         Kensington lock port           TachStation         Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry Pl, EZ Cast Pro Dongle and other HDMI devices           Throw Alzon           1 Intel Maximum         1 m           1 hrow Ratio – Maximum         1 m           1 hrow Ratio – Maximum         2 left           2 coung         4 y x 9.3 x 12.3 in / 12.45 x 236.2 x 312.4 mm	Control	RS232, IR Remote
3D Support         1080p @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required           Power Consumption         300.0W max           Power Consumption – Low Power Standby Mode         1.8W max           Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         220.0W max           Power Standard         AC 100 to 240V, 50/60           Operating Conditions         31 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese           Menu Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hund, Filipino, Farsi, Japanese, Thai           Security Features         Kensington lock port           TechStation         Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Aschromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw and Zoon           Throw Distance – Minimum         1 m           Throw Ratio – Maximum         12 m           1950 Maximum         2.16:1           Zoon Rati	Audible Noise – Eco Mode	< 21 dBA at 0°F / -17.8°C
Power Consumption         300.0W max           Power Consumption – Standby Mode         18W max           Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         220.0W max           Power Standard         AC 100 to 240V, 50/60           Operating Conditions         1 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese           Menu Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Krean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai           Security Features         Kensington lock port           Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw Distance – Minimum         1 m           Throw Ratio – Minimum         1.94:1           Throw Ratio – Maximum         2 m           Throw Ratio – Maximum         4.9 × 9.3 x 12.3 in / 12.4 to 12.5 to	Included Accessories	Power cord, Remote, HDMI Cable, Documentation, User Manual (CD)
Power Consumption – Standby Mode         1.8W max           Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         220.0W max           Power Standard         ACt 100 to 240V, 50/60           Operating Conditions         41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese           Menu Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindit, Filipino, Farsi, Japanese, Thai           Security Features         Kensington lock port           Throw And Zoom         Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Saus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw Distance – Minimum         1 m           1 hrow Ratio – Minimum         1 m           1 hrow Ratio – Minimum         1 p.94:1           1 hrow Ratio – Maximum         2 lei:1           2 brown Ratio – Maximum         2 lei:1           2 brown Ratio – Maximum         4.9 x 9.3 x 12.3 in / 12.4 x 2.36.2 x 312.4 mm           Product Dimensions         4.9 x 9.3 x 12.3 in / 12.4 x 2.36.2 x 312.4 mm     <	3D Support	1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required
Power Consumption – Low Power Standby         0.5W max           Power Consumption – Eco Mode         220.0W max           Power Standard         AC 100 to 240V, 50/60           Operating Conditions         41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinnish, Arabic, Indonesian, Portuguesee           English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hilot, Fillipin, Farsi, Japanese, Thai           Security Features         Kensington lock port           TechStation         Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw And Zoom         1           Throw Distance – Minimum         1 m           Throw Ratio – Maximum         1.94:1           Throw Ratio – Maximum         2.16:1           Zoom Ratio         1.1           Shipping         4.9 x 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm           Product Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption	300.0W max
Power Consumption – Eco Mode         220.0W max           Power Standard         AC 100 to 240V, 50/60           Operating Conditions         41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese           Menu Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai           Security Features         Kensington lock port           Throw And Zoom         Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw Distance – Maximum         1 m           1hrow Ratio – Minimum         1 M           1hrow Ratio – Minimum         1.94:1           1hrow Ratio – Maximum         2.16:1           2oom Ratio         1.1:1           Shipping         4.9 x 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm           Product Dimensions         4.9 x 9.3 x 12.3 in / 19.5 3.2 kg           Shipping Dimensions         7.7 x 13.3 x 15.5 in / 19.5 6 x 337.8 x 398.8 mm	Power Consumption – Standby Mode	1.8W max
Power Standard         AC 100 to 240V, 50/60           Operating Conditions         dt 10/4" at 0 to 100000 ft / 5 to 40°C at 0 to 3048 m           Documentation Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese           Menu Languages         English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai           Security Features         Kensington lock port           TechStation         Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices           Throw and Zoom         1 m           Throw Distance – Minimum         1 m           Throw Ratio – Minimum         1 94:1           Throw Ratio – Maximum         2 16:1           Zoom Ratio         1:1           Shipping         49 × 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm           Product Dimensions         47 x 11s / 3.2 t 5.7 in / 195.6 x 337.8 x 398.8 mm	Power Consumption – Low Power Standby	0.5W max
Operating Conditions41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and Zoom1 mThrow Distance – Maximum1 2 mThrow Ratio – Maximum1.94:1Throw Ratio – Maximum2.16:1Zoom Ratio1.1:1ShippingVorduct Dimensions49 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mmProduct Dimensions4.7 × 13.3 × 15.7 in / 195.6 × 3378 × 398.8 mm	Power Consumption – Eco Mode	220.0W max
Operating Conditions5 to 40°C at 0 to 3048 mDocumentation LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Frinnish, Arabic, Indonesian, PortugueseMenu LanguagesEnglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationKensington lock portThrow and ZoomWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow Distance – Minimum1 mThrow Distance – Maximum1.94:1Throw Ratio – Minimum1.94:1Throw Ratio – Maximum2.16:1Zoom Ratio1.1:1ShippingProduct Dimensions49 × 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Power Standard	AC 100 to 240V, 50/60
Finnish, Arabic, Indonesian, Portuguese  English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Pollish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindir, Filipino, Farsi, Japanese, Thai  Security Features Kensington lock port  TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices  Throw and Zoon  Throw Distance – Minimum 1 m  Throw Distance – Maximum 12 m  Throw Ratio – Minimum 1.94:1  Throw Ratio – Maximum 2.16:1  Zoom Ratio 1.1:1  Shipping  Product Dimensions 4.9 x 9.3 x 12.3 in /  12.45 x 236.2 x 312.4 mm  Product Weight 7.1 lbs / 3.2 kg  Shipping Dimensions 7.7 x 1.3.3 x 15.7 in /  195.6 x 337.8 x 398.8 mm	Operating Conditions	,
Menu LanguagesRussian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, asc Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomThrow Distance – Minimum1 mThrow Distance – Maximum12 mThrow Ratio – Minimum1.94:1Throw Ratio – Maximum2.16:1Zoom Ratio2.16:1Zoom Ratio1.1:1ShippingProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Documentation Languages	
TechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoomThrow Distance – Minimum1 mThrow Distance – Maximum12 mThrow Ratio – Minimum1.94:1Throw Ratio – Maximum2.16:1Zoom Ratio1.1:1ShippingProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Menu Languages	Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian,
Throw and Zoom Throw Distance – Minimum 1 m Throw Distance – Maximum 12 m Throw Ratio – Minimum 1.94:1 Throw Ratio – Maximum 2.16:1 Zoom Ratio	Security Features	Kensington lock port
Throw Distance – Minimum         1 m           Throw Distance – Maximum         1.94:1           Throw Ratio – Maximum         2.16:1           Zoom Ratio         1.1:1           Shipping           Product Dimensions         4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm           Product Weight         7.1 lbs / 3.2 kg           Shipping Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	TechStation	
Throw Distance – Maximum         12 m           Throw Ratio – Minimum         1.94:1           Throw Ratio – Maximum         2.16:1           Zoom Ratio         1.1:1           Shipping           Product Dimensions         4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm           Product Weight         7.1 lbs / 3.2 kg           Shipping Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw and Zoom	
Throw Ratio – Minimum       1.94:1         Throw Ratio – Maximum       2.16:1         Zoom Ratio       1.1:1         Shipping         Product Dimensions       4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm         Product Weight       7.1 lbs / 3.2 kg         Shipping Dimensions       7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Minimum	1 m
Throw Ratio – Minimum       1.94:1         Throw Ratio – Maximum       2.16:1         Zoom Ratio       1.1:1         Shipping         Product Dimensions       4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm         Product Weight       7.1 lbs / 3.2 kg         Shipping Dimensions       7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Distance – Maximum	12 m
Zoom Ratio         1.1:1           Shipping           Product Dimensions         4.9 x 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm           Product Weight         7.1 lbs / 3.2 kg           Shipping Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Minimum	
Shipping           Product Dimensions         4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm           Product Weight         7.1 lbs / 3.2 kg           Shipping Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Throw Ratio – Maximum	2.16:1
Product Dimensions         4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm           Product Weight         7.1 lbs / 3.2 kg           Shipping Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Zoom Ratio	1.1:1
Product Dimensions       124.5 x 236.2 x 312.4 mm         Product Weight       7.1 lbs / 3.2 kg         Shipping Dimensions       7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Shipping	
Product Weight         7.1 lbs / 3.2 kg           Shipping Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Product Dimensions	
Shipping Dimensions         7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm	Product Weight	
		7.7 x 13.3 x 15.7 in /
	Shipping Weight	

<sup>\*</sup> Product specifications, terms, and offerings are subject to change at any time without notice.

### Accessories

SimpleShare Presentation System (INA-SIMPS1)
Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)
DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
Soft Carry Case for Value Projectors (CA-SOFTVAL-2)
SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

SimpleShare Transmitter (INA-SIMTM1)

SimpleShare Receiver (INA-SIMRC1)

SimpleShare Transmitter with Paired USB Touch Adapter (INA-SIMTTM1)

SimpleShare Interactive Receiver (INA-SIMRINT1)

SimpleShare Charging Station (INA-SIMCH1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)