IN136

InFocus

The Superpowered Projector Designed for Use with Google Chromecast and Other Devices Part #: IN136

The InFocus IN136 WXGA projector combines stellar image performance, long-life lamp and low cost with the ability to create a more powerful and dynamic education experience. Simply insert your Google ChromeCast, Intel Computer Stick, Android solution, or other device into the projector's TechStation internal HDMI 1.4 bay and turn your projector into an all-in-one classroom solution.

Key Features

- ♦ WXGA (1280 x 800) resolution
- TechStation lets you customize your projector with the devices you already use
- ♦ Powered HDMI for mobile charging and device power
- 28,500:1 contrast ratio and up to 4000 lumens for depth of image and life-like colors
- ♦ Long life lamp of up to 15,000 hours
- Class-leading, whisper-quiet design















Customize your projector using TechStation

With an HDMI port and multiple ways to connect your devices, the TechStation superpowers your projector and enables more effective learning by working seamlessly with the tools you already use. After connecting your device, close up the TechStation's lid to create a streamlined, all-in-one solution for streaming audio and video.

IN130 Series projectors work with:

- Google ChromeCast Ultra
- Intel Computer Stick
- Asus Chromebit
- Amazon Fire TV Stick
- Android stick

 And more HDMI-supported devices to enable casting, streaming, and wireless



when not in use, and save even more money over the life of the projector.

Over 1 Billion Colors

BrilliantColor™ DLP imaging technology lets images shine with over 1 billion colors that ensure life-like color accuracy and eyecatching presentations. Get better, brighter images on whiteboards, blackboards, or beige walls, in any light.

Engage Audiences from Every Angle with 3D

Bring content to life with support for multiple forms of 3D -- including Blu-Ray, 3D broadcasting, videos games and PC connectivity. All your audience needs are 144Hz DLP Link 3D glasses (sold separately).



Quietest Projector in its Class

Make sure students always hear the lessons, not the fans. With only 21dB in eco mode, IN136 projector was designed to be quieter, with Smooth Flow fan technology, a cooling-efficient enclosure, and silent bearings.

Save Energy with Value that Lasts

IN130 projectors are designed to fit your budget go the distance with ultra-long lamp life of up to 15,000 hours and no filters to clean or replace. Unlike other imaging technologies, the TI DLP* chip ensures no image decay over time so your projector lasts longer. Activate Dynamic Mode to dim the image

Easy to Install and Manage

Quickly and simply install and manage your projector over your school's network with free ProjectorNet 4.1 software from InFocus, or choose to utilize Crestron Roomview or AMX Device Discovery.

Specifications*

| Projector | IN136 |
|------------------------------|---|
| Resolution – Native | WXGA (1280 x 800) |
| Display Technology | DLP |
| Video Standard Compatibility | NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| Speakers | Mono 10W x 1 |
| Lamp Brightness | 4,000 lumens |
| Lamp Brightness – Eco Mode | 3,200 lumens |
| Lamp Life | 5,500 hours |
| Lamp Life – Low Power | 10,000 hours |
| Lamp Life – Dynamic Mode | 15,000 hours |
| Lamp Power | 245W |

| Lamp Power Eco Mode | Projector | IN136 |
|--|---------------------------------------|---|
| Color Wheel High Speed 6 Segment RYGCWB Number of Colors 1.70 billen Synch Scan Frequency - Horizontal 31.5 ° 976 R42 Synch Scan Frequency - Vertical 56 - 120 KH2 Aspect Ratio Compatibility 43, 1693, 2361, 11, 21, 129, 159, 54 Projection Lans F Stop - Maximum 2.50 Projection Lans F Stop - Maximum 2.57 Lens Ype Manual focus Image Size - Maximum 2.56 in Projection Lans F Stop - Maximum 2.56 in Projection Gere Minimum 2.56 in Image Size - Maximum 2.56 in Projection Giffer 1.24 % ~ 5% V Keyston Correction 4.07 V Connectors - Inputs 3.5mm audio output, Monter out (VGA) Control 6.523, IR Remote Aub ble Noise - Eco Midde 2.21 GBA at 10° 7 / 178°C Included Accessories 9.0wer consumption 2.00 Wmax Power Consumption 2.00 Wmax Power Consumption - Eco Mode 2.21 GBA at 10° 7 / 178°C Operating Conditions 3.00 Wmax Power Consumption - Eco Mode 2.00 Wmax | Lamp Power – Eco Mode | 170W |
| Number of Colors 107 billion Synch Scan Frequency – Horizontal 31.5" 97.5 KHz Synch Scan Frequency – Vertical 66 - 120 kHz Aspect Ratio 43. 169.2 sizk. 15, 2-1, 139, 159, 54 Aspect Ratio Compatibility 43. 169.2 sizk. 15, 2-1, 139, 159, 54 Projection Lens F-Stop – Minimum 2.50 Lens Type Manual Focus Image Size – Minimum 23 in Image Size – Maximum 23 in Projection Offset 12.4% ~ 5% V Keystane Correction 4.40°V Connectors – Dutouts 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 14a 3D support), USB-A (TechStation Connection) Connectors – Dutouts 3.5mm audio output, Monitor out (VGA) Controll 8.523.1 (R Reme Audible Noise – Eco Mode < 21 dBA of VF / PSC | , | 28,500:1 |
| Synch San Frequency - Horizontal 31.5 ° 97.6 KHz Synch San Frequency - Vertical 56 - 120 KHz Aspect Ranio Compatibility 43. 1682_354.1 3.2 1, 13.9, 15.9, 5.4 Projection Lens F Stop - Maximum 2.67 Fregitan Stop - Maximum 2.8 in Lens Type Manual focus Image Size - Maximum 2.9 in Projection Offset 11.2 4% + 5% V Keystone Correction 4.40 V Connectors - Inputs 3.5 mm audio, Composite video, VGA, HDM11.4a x3 (with 1.4a x3D support), USB A (TechStation Connection) Control 8.23 mm audio output, Monitor out (VGA) Control 8.23 kB Remote Audible Noise - Eco Mode < 21 offs A or V7 - 78 ffc | Color Wheel | High Speed 6 Segment RYGCWB |
| Synch Scan Frequency – Vertical 56 - 120 KHz Aspect Ratio 16:10 Aspect Ratio Compatibility 43, 163, 2.56, 1.1, 21, 13.9, 16.9, 5.4 Projection Lens F-Stop – Minimum 2.50 Iners Type Manual focus Image Size – Minimum 2.3 in Lens Type Manual focus Projection Offset 112.4% - 5% V Keystone Correction 4.07 Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Composite video, VGA, HDMI 14a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Control (Included Accessories) 9.0me consumption Audible Noise – Eco Mode < 21 clBA at 0.0% 1.12 (EC) | Number of Colors | 1.07 billion |
| Aspect Ratio 16:10 Aspect Ratio Compatibility 43, 16:39, 2:35:1, 11, 2:1, 13:9, 15:9, 5:4 Projection Lens F Stop – Minimum 2:6 Projection Lens F Stop – Maximum 2:6 Lens Type Manual focus Image Size – Maximum 2:8 in Projection Offset 11:24% - 5% V Keystone Correction 1:4 dV Connectors – Inputs 3:5mm audio composite video, VGA, HDMI 14:a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Conrectors – Outputs 3:5mm audio composite video, VGA, HDMI 14:a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Control 85:232, IR Remote Audible Noise – Eca Mode 2:1 dBA at 07:17:8°C Included Accessories 9 over consumption 3:5 support 108:00 g 6 GHz, All HDMI 14:a 3D formats, DLP Link 3D glasses required Power Consumption – Standby Mode 18W max Power Consumption – Standby Mode 18W max Power Consumption – Eca Mode 2:0.0 W max Power Consumption – Eca Mode 2:0.0 W max Power Consumption – Eca Mode 2:0.0 W max Power Standard AC 10:0 to 24:0V, 50:60 Opera | Synch Scan Frequency – Horizontal | 31.5 ~ 97.6 KHz |
| Aspect Ratio Compatibility 4.3 16.9, 2.35.1, ht. 2.1 13.9, 15.9, 5.4 Projection Larse F-Stop – Mainimum 2.50 Lars Type Manual focus Image Size – Maximum 25 in Image Size – Maximum 256 in Projection Offset 112.4% + 5% V Kaystane Correction 40V Connectors – Inputs 3.5mm audio output, Monitor out (VGA) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Renote Audible Noise – Eco Mode < 21 cBA at 0°F / 178°C | Synch Scan Frequency – Vertical | 56 - 120 KHz |
| Projection Lens F-Stop – Minimum 2.67 Projection Lans F-Stop – Maximum 2.67 Lanse Type Manual focus Inage Size – Minimum 23 in Lange Size – Maximum 256 in Projection Offset 112.4% + 5% V Keystone Correction 4 0V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDM1 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Control 8.523.2 IR Remote Audible Noise – Eco Mode < 21 dBA at 0°T / 178°C | Aspect Ratio | 16:10 |
| Projection Lans F Stop – Maximum 267 Lans Type Manual focus Lans Expe – Minimum 23 in Image Size – Maximum 256 in Projection Offset 12.4% + 5% V Keystone Correction 4 0°V Connectors – Inputs 3 5mm audio Composite video, VGA, HDM1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Output 35mm audio coutput, Monitor out (VGA) Control RS232, IR Remote Audibin Noise – Eco Mode 42 rd BA at 0°F / 178°C Included Accessories Power Corn Summer, HDMI Cable, Documentation, User Manual (CD) 3D Support 9090 @ 60Hz, All HDM1.4a 3D formats, DLP Link 3D glasses required Power Consumption – Standby Mode 18W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Low Power Standby 0.100 to 240V, 50/50 Ocerating Conditions 41 to 104°F at 0 to 100000 ft / 5 to 40°C at 0 to 30.48 m Documentation Languages English, Franch, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Fininsky, Arabic, Indonesian, Portuguese Recurity Features Kores | Aspect Ratio Compatibility | 4:3, 16:9, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4 |
| Lens Type Manual focus Inage Size – Minimum 23 in Inage Size – Minimum 256 in Projection Offset 112.4% + 5% V Koystone Carrection ± 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDM1 L4a x3 (with L4a 3D support), USB A [TechStation Connection] Control 8.5mm audio output, Monitor out (VGA) Control RS 232, IR Remote Audible Noise – Econ Mode < 21 dBA at 07 + 18°C | Projection Lens F-Stop – Minimum | 2.50 |
| Image Size – Minimum 23 in Image Size – Maximum 256 in Projection Offset 12 4% + 5% V Keystone Correction ± 40°V Connectors – Outputs 3.5mm audio, Composite video, VGA, HDM1.4a x3 (with 1.4a x3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio, Output, Monitor out (VGA) Connectors – Outputs 3.5mm audio, Output, Monitor out (VGA) Control 8232, IR Remote Audible Noise – Eco Mode < 21 dBA at 0°F / 178°C | Projection Lens F-Stop – Maximum | 2.67 |
| Image Size – Maximum | Lens Type | Manual focus |
| Projection Offset 112.4% + 5% V Keystone Correction ± 40°V Connectors – Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors – Outputs 3.5mm audio output, Monitor out (VGA) Control 85.232, IR Remote Audible Noise – Eco Mode < 21 dBA at OFF -/128°C Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 30 Support 10800 @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Exo Mode 1.8W max Power Consumption – Eco Mode 2.20.0W max Power Consumption – Eco Mode 2.20.0W max Power Standard AC 100 to 2.40V, 50/60 Operating Conditions English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Flijieno, Farsi, Japanese, Thai Security Features Kensington lock port Trow Distance – Maximum <td>Image Size – Minimum</td> <td>23 in</td> | Image Size – Minimum | 23 in |
| Keystone Correction ± 40°V Connectors – Inputs 3.5 mm audio output, Monitor out (VGA) Connectors – Outputs 3.5 mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise – Eco Mode < 21 dBA at OT / 178°C | Image Size – Maximum | 256 in |
| Connectors - Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audiblo Noise - Eco Mode <21 dBA at OFF /-178°C | Projection Offset | 112.4% +- 5% V |
| Connectors - Inputs 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) Connectors - Outputs 3.5mm audio output, Monitor out (VGA) Control RS232, IR Remote Audible Noise - Eco Mode < 21 dBA at 0°F /-17.8°C | , | ± 40°V |
| Connectors - Outputs 3.5mm audio output, Monitor out (VGA) Control 82323, IR Remote Audible Noise - Eco Mode < 21 dBA a OTF /-17.6°C | • | 3.5mm audio, Composite video, VGA, HDMI 1.4a x3 (with 1.4a 3D support), USB-A (TechStation Connection) |
| Audible Noise — Eco Mode < 21 dBA at 0"F / -17.8"C | Connectors – Outputs | 3.5mm audio output, Monitor out (VGA) |
| Included Accessories Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) 3D Support 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Halyarian, Malay, Hind, Elipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Romanian, Hungarian, Malay, Hind, Elipino, Farsi, Japanese, Thai Throw Distance – Minimum 1 m Throw Ratio – Maximum 1 m Throw Ratio – Maximum 1 54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:4 | Control | RS232, IR Remote |
| 3D Support 1080p @ 60Hz, All HDMI 14a 3D formats, DLP Link 3D glasses required Power Consumption 300.0W max Power Consumption – Low Power Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 31 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hunding, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Such romebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Minimum 1 m Throw Alzon 1.54-1 Throw Ratio – Maximum 1.52-1 Town Ratio – Maximum 1.72-1 Zoom Ratio 1.1 Thips/3.2 kg | Audible Noise – Eco Mode | < 21 dBA at 0°F / -17.8°C |
| Power Consumption 300.0W max Power Consumption – Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Becurity Features English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock, port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Minimum 1 m Throw Ratio – Maximum 1.54:1 Throw Ratio – Maximum 1.54:1 Throw Ratio – Maximum 1.52:1 Toma Ratio – Minimum 49 × 9.3 x 12.3 in / 12.4 to 2.4 | Included Accessories | Power cord, Remote, HDMI Cable, Documentation, User Manual (CD) |
| Power Consumption – Standby Mode 1.8W max Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard 4.0 100 to 240V, 50/60 Operating Conditions 41 to 104°F at 0 to 100000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Pollish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Security Features Kensington lock port Throw Distance – Minimum 1 m 1 hrow Distance – Minimum 1 m 1 hrow Ratio – Maximum 1.54:1 1 hrow Ratio – Maximum 1.54:1 2 towards 1.54:1 2 towards 1.54:1 3 towards 1.54:1 4 towards 1.54:1 4 towards 1.54:1 5 towards 1.54:1 6 towards | 3D Support | 1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required |
| Power Consumption – Low Power Standby 0.5W max Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 21 to 104°F at 0 to 100000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Sussian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port Security Features Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Sus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Minimum 1 m 1 frow Ratio – Maximum 1 0 m 1 frow Ratio – Maximum 1 1.54.1 2 foom Ratio 1.52.1 2 foom Ratio 1 2.52.1 2 foom Ratio 1 2.52.2 2 footuct Dimensions 4.9 × 9.3 × 12.3 in / 12.4 × 23.6 z × 312.4 mm Product Weight 7 1 lbs / 3.3 x 15.7 in / 195.6 × 337.8 × 398.8 mm | Power Consumption | 300.0W max |
| Power Consumption – Eco Mode 220.0W max Power Standard AC 100 to 240V, 50/60 Operating Conditions 3t to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw Distance – Maximum 1 m 1hrow Ratio – Minimum 1.54:1 1hrow Ratio – Maximum 1.54:1 2oom Ratio 1.12 Shiping 4.9 x 9.3 x 12.3 in / 12.45 x 236.2 x 312.4 mm Product Dimensions 4.9 x 9.3 x 12.3 in / 12.45 x 236.2 x 312.4 mm Shipping Dimensions 7.7 x 13.3 x 15.7 in / 19.56 x 337.8 x 398.8 mm | Power Consumption – Standby Mode | 1.8W max |
| Power Standard AC 100 to 240V, 50/60 Operating Conditions 21 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoom 1 m 1hrow Distance – Minimum 1 m 1hrow Ratio – Minimum 1.54:1 1hrow Ratio – Maximum 1.72:1 2oom Ratio 1.12 Shipping 4.9 × 9.3 × 12.3 in / 12.4 s × 236.2 x 312.4 mm Product Dimensions 4.9 × 9.3 × 12.3 in / 12.4 s × 236.2 x 312.4 mm Shipping Dimensions 7.7 × 13.3 × 15.7 in / 19.5 6 × 337.8 x 398.8 mm | Power Consumption – Low Power Standby | 0.5W max |
| Operating Conditions 41 to 104°F at 0 to 10000 ft / 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoon Throw Distance – Maximum 1 m 1 hrow Ratio – Maximum 1.54:1 1 com Ratio 1.52:1 2 com Ratio 1.51:1 2 com Ratio 1.52:1 2 com Ratio 1.51:1 Shipping Product Dimensions 1.51 (3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Power Consumption – Eco Mode | 220.0W max |
| Operating Conditions 5 to 40°C at 0 to 3048 m Documentation Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Finnish, Arabic, Indonesian, Portuguese Menu Languages English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Russian, Finnish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoon Throw Distance – Minimum 1 m Throw Distance – Maximum 1.0 m 1.54:1 1.54:1 Zoom Ratio 1.54:1 Zoom Ratio 1.1:1 Shipping 4.9 x 9.3 x 12.3 in / 12.4 5 x 236.2 x 312.4 mm Product Dimensions 7.7 x 13.3 x 15.7 in / 19.5 6 x 337.8 x 398.8 mm | Power Standard | AC 100 to 240V, 50/60 |
| Finnish, Arabic, Indonesian, Portuguese Renglish, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hugarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai Security Features Kensington lock port TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw and Zoon Throw Distance – Minimum 1 m Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 × 9.3 × 12.3 in / 124.5 × 236.2 × 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 × 1.3.3 × 15.7 in / 195.6 × 337.8 × 398.8 mm | Operating Conditions | |
| Menu LanguagesRussian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, ThaiSecurity FeaturesKensington lock portTechStationWorks with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devicesThrow and ZoonThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum1.54:1Throw Ratio – Maximum1.72:1Zoom Ratio1.72:1Zoom Ratio1.1:1Product Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmProduct Weight7.1 lbs / 3.2 kgShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Documentation Languages | |
| TechStation Works with Google Chromecast, Chromecast Ultra, Amazon Fire Stick, Android TV Stick, InFocus SimpleShare, Asus Chromebit, Intel PC Stick, Raspberry PI, EZ Cast Pro Dongle and other HDMI devices Throw And Zoom Throw Distance – Minimum 1 m 10 m 11 m 11 m 11 m 11 m 11 m 11 m | Menu Languages | Russian, Finnish, Polish, Turkish, Danish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, |
| Throw and ZoomThrow Distance – Minimum1 mThrow Distance – Maximum10 mThrow Ratio – Minimum1.54:1Throw Ratio – Maximum1.72:1Zoom Ratio1.1:1ShippingProduct Dimensions4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mmShipping Dimensions7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Security Features | Kensington lock port |
| Throw Distance – Minimum 1 m Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | TechStation | |
| Throw Distance – Maximum 10 m Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Throw and Zoom | |
| Throw Ratio – Minimum 1.54:1 Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Throw Distance – Minimum | 1 m |
| Throw Ratio – Maximum 1.72:1 Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Throw Distance – Maximum | 10 m |
| Zoom Ratio 1.1:1 Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Throw Ratio – Minimum | 1.54:1 |
| Shipping Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Throw Ratio – Maximum | 1.72:1 |
| Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Zoom Ratio | 1.1:1 |
| Product Dimensions 4.9 x 9.3 x 12.3 in / 124.5 x 236.2 x 312.4 mm Product Weight 7.1 lbs / 3.2 kg Shipping Dimensions 7.7 x 13.3 x 15.7 in / 195.6 x 337.8 x 398.8 mm | Shipping | |
| 7.7 x 13.3 x 15.7 in / Shipping Dimensions 195.6 x 337.8 x 398.8 mm | Product Dimensions | |
| 7.7 x 13.3 x 15.7 in / Shipping Dimensions 195.6 x 337.8 x 398.8 mm | Product Weight | |
| Shipping Weight 9.9 lbs / 4.5 kg | | 7.7 x 13.3 x 15.7 in / |
| | Shipping Weight | 9.9 lbs / 4.5 kg |

^{*} Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

SimpleShare Presentation System (INA-SIMPS1)
Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
1 Year Extended Warranty for IN1XX Projectors (EPW-PJV1)
DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)
Soft Carry Case for Value Projectors (CA-SOFTVAL-2)
SimpleShare (INA-SIMS1)

SimpleShare Touch Presentation System (INA-SIMINT1)

SimpleShare Transmitter (INA-SIMTM1)

SimpleShare Receiver (INA-SIMRC1)

SimpleShare Transmitter with Paired USB Touch Adapter (INA-SIMTTM1)

SimpleShare Interactive Receiver (INA-SIMRINT1)

SimpleShare Charging Station (INA-SIMCH1)

LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)

2 Year Extended Warranty for IN1XX Projectors (EPW-PJV2)