

CinemaX D2 Smart

Laser Projection TV*









- True 4K UHD resolution with 8.3 million on-screen pixels - HDR and HLG compatibility with HDR brightness adjustment
- Big-screen 100-inch images from less than a foot away with an ultra-short throw lens - Low lag gaming - 16ms in 4K at 60Hz and 4ms in 1080P at 240Hz
- Simplify your entertainment experience with Android TV™ - Enjoy access to 400,000+ movies, TV shows, live sports, and play music and games across streaming services
- Easy setup with geometry correction 3x3 warping function - Built-in 20W audio supports eARC



Smart 4K UHD ultra short throw projection

Easy access to everything you want to watch.

Simplify your entertainment experience with Android TV™ on the CinemaX D2 Smart ultra short throw projector. Enjoy access to 400,000+ movies, TV shows, live sports, and play music and games across streaming services and even customize your home screen to display

Specifications

Power supply

Net weight

Power consumption (standby)
Power consumption (min)

Power consumption (max)

Dimensions (W x D x H) Gross weight

Weight and dimensions

opecifications	
EAN: 5055387666054, Colour: Black	
EAN: 5055387666061, Colour: White	
UPC: 796435 81 449 6, Colour: Black	
UPC: 796435 81 448 9, Colour: White	
Display/image	6
Display/image Display technology	DI P™
Resolution	UHD (3840x2160)
Brightness	3,000 lumens
Contrast ratio	1,800,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction -	10°
horizontal	
Keystone correction - vertical	10°
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	90%
Screen size	85" ~ 120" diagonal
Lamp info	
Light source type	Laser
LASER life	30,000 hours
Optical	
Throw ratio	0.25:1
Projection distance	18.5" - 25.98"
Focal length (mm)	525mm/20.669"
Native offset	124%
Connectivity	
Connections	Inputs 3 x HDMI 2.0
-	Inputs 3 x HDMI 2.0 Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio
-	•
-	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio
Connections	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio
Connections	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm
General Noise level (typical)	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA,
General Noise level (typical) Noise level (max)	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SYGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz),
General Noise level (typical) Noise level (max) PC compatibility	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p,
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 2
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WOHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humicity 85% Backlit home remote 2 10W AC power cord 2x AAA batteries
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 2 10W AC power cord 2x AAA batteries Basic user manual
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D Security OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 2 10W AC power cord 2x AAA batteries Basic user manual android TV stick & remote
General Noise level (typical) Noise level (max) PC compatibility 2D compatibility 3D compatibility 3D compatibility OSD / display languages Operating conditions Remote control Speaker count Watts per speaker	Outputs 1 x S/PDIF, 1 x USB-A power 1.5A, 1 x Audio 3.5mm 26dB 28dB UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 480l/p, 576l/p, 720p(50/60Hz), 1080l(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) Frame-pack: 1080p24, 720p50 / 60 Frame sequential: 1080p, WXGA, XGA, SVGA 120Hz 3D ready Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85% Backlit home remote 2 10W AC power cord 2x AAA batteries Basic user manual

100 ~ 240V, 50 ~ 60Hz

22.68" x 15.08" x 5.12"

0.5W

190W

230W

25.35 lbs

18.52 lbs







